EVOCHARGE™

LEVEL 2 EVSE CHARGING STATIONS

- **Up to 8X Faster than Level 1**
- **SAE J1772**
- **208-240VAC Single Phase 40A Supply Circuit**
- **7.2 – 7.7 kW**
- **Modern Compact Design and Durability**
- **Indoor and Outdoor Use – NEMA 4 rated**
- **Multiple Cord Length Options**
- **Adjustable Maximum Current Output:** 32A, 30A, 24A, 16A (to support multiple circuit ratings 40A, 30A, 20A)
- **Single and Dual Station Options**
- **Hardwire or Inlet Adapter – NEMA 6-50 Plug**
- **Wall or Pedestal Mount**

Product Selections	Features	EVSE	iEVSE®	iEVSE Plus
Non-Networked	Standard Model—No Network Capability	✔		
Wi-Fi Enabled	▪ Access Control ▪ Control Data Collection ▪ Demand Response ▪ Local Load Management ▪ Mobile App Capability ▪ Remote Monitoring		✔	✔
Wi-Fi & LTE Cellular				✔
RFID Technology	Supports RFID Card Access Control & User Authorization			✔

Cable Management Options

Charging Station c UL us

EVOREEL with Cable c ETL us

Cable Retractor

EVOREEL® with Charge Cable

Dual Port 6 ft. Pedestal with EVOREEL®

Single Port 4 ft. Pedestal

9700 West 74th Street, Eden Prairie, MN 55344
Phone: 952-941-9700 ▪ **Toll-Free:** 800-328-6108
evochargesales@phillipsandtemro.com

 # LIT0244 ©2020 PHILLIPS & TEMRO INDUSTRIES PRINTED IN U.S.A.

PHILLIPS & TEMRO industries®

www.phillipsandtemro.com