

EVOCHARGE® Cable Management Solutions

Product Description and Specifications

ELECTRIC VEHICLE CABLE MANAGEMENT

- **Modern Compact Design:** convenient design for clean, safe management of charging cable
- **Connection Options:** Simple connection of EVOREEL to EVSE's, interconnect cable options – 3 ft. (standard) and 20 ft. (optional)
- **Robust Construction, Certified for Outdoor Use:** NEMA 4 certified for outdoor and indoor use
- **EVOREEL®:** self-retracting and locking reel
- **Retractor:** spring loaded tether, suspends cable to effortlessly draw back cable for convenient storage
- **EVOREEL Cable Management:** cable length options available: 22 ft. (standard) and 30 ft. (optional)
- **Flexible Mounting Options:** mount to wall, overhead, or pedestal/ground installation.



Part Number	EVOREEL Hardwire EVC0101B, Optional charging cable and interconnect cables available.
Connector / EVSE Level	SAE J1772; AC Level 2
Max Output Rating	EVOREEL 24A; 5.8 kW Maximum Output – For use with dedicated 40A (or greater) Supply Circuit
Operational Ratings	NEMA 4, Indoor/Outdoor Rated; Temp: -22°F to 122°F (-30°C to 50°C); Humidity: 95% RH
Mounting	Overhead and Pedestal Installation (single or dual mount)
Dimensions	EVOREEL 13.8 x 12.0 x 9.2 inches (35.1 x 30.5 x 23.4 cm), Retractor 9 x 3 x 6 inches (22.9 x 7.6 x 15.2 cm)

*visit phillipsandtemro.com for more information or to download an installation manual