

# Level 2 EVSE Charging Stations

## FEATURES

### PRODUCT FEATURES

Modern compact design with robust construction for maximum durability

- Up to 8X Faster than Level 1
- SAE J1772
- 208-240VAC Single Phase
- 32A and 40A options
- Modern Compact Design and Durability
- Indoor and Outdoor Use – NEMA 4 rated
- Multiple Cord Length Options
- Adjustable Maximum Current Output: 32A, 24A, 16A (to support multiple circuit ratings 40A, 30A, 20A)
- Option to Mount Up to Four Stations
- Hardwire or Inlet Adapter – NEMA 6-50 Plug
- Wall or Pedestal Mount



Features	EVSE	iEVSE® Home		iEVSE®		iEVSE Plus	
Max Power Output	32A	32A	40A	32A	40A	32A	40A
Non-networked	✓						
WiFi		✓	✓	✓	✓	✓	✓
Mobile App Capability*		✓†	✓†	✓	✓	✓	✓
Remote Monitoring*		✓†	✓†	✓	✓	✓	✓
Access Control*				✓	✓	✓	✓
Local Load Management				✓	✓	✓	✓
Ethernet Connection					✓		✓
RFID Technology						✓	✓
LTE Cellular Connectivity						✓	✓

\* With network service provider subscription  
 † With EvoCharge mobile app

### Accessories



Cable Retractor



EvoReel® with Charge Cable



Dual Port 6 ft. Channel Pedestal with EvoReel®



Single Port 4 ft. Concealed Pedestal

