

Level 2 EVSE Charging Stations

FEATURES

PRODUCT FEATURES

Modern compact design with robust construction for maximum durability

- Up to 8X Faster than Level 1
- SAE J1772
- 208-240VAC Single Phase 40A Supply Circuit
- 32A and 40A options
- Modern Compact Design and Durability
- Indoor and Outdoor Use – NEMA 4 rated
- Multiple Cord Length Options
- Adjustable Maximum Current Output: 32A, 24A, 16A (to support multiple circuit ratings 40A, 30A, 20A)
- Option to Mount Up to Four Stations
- Hardwire or Inlet Adapter – NEMA 6-50 Plug
- Wall or Pedestal Mount



Features	EVSE	iEVSE Home		iEVSE®		iEVSE Plus
Max Power Output	32A	32A	40A	32A	40A	32A
Non-networked	✓					
WiFi		✓	✓	✓	✓	✓
Mobile App Capability*		✓ [†]	✓ [†]	✓	✓	✓
Remote Monitoring*		✓ [†]	✓ [†]	✓	✓	✓
Access Control*				✓	✓	✓
Local Load Management				✓	✓	✓
Ethernet Connection			✓		✓	
RFID Technology						✓
LTE Cellular Connectivity						✓

* With network service provider subscription
 † With EvoCharge mobile app

Cable Management Options

