

# Credit Card Reader Kiosk

## Specification Sheet

### ELECTRIC VEHICLE CHARGING STATION PEDESTAL

Ground-mounted credit card payment kiosk. Used with networked charger installations requiring physical card readers on site. Compatible with any NSP network that supports Payter payment solutions.

- Small 6 in. x 6 in. footprint
- 3.5-inch LCD touch screen
- 4G LTE connection
- IK09 impact rated

<b>Contactless Interface</b>	EMVCo. L1 v33.0 Certificate ISO14443 Type A & B (T=CL) Mifare Classic protocol Desfire protocol EV2/3 ISO18092: Support NFC protocol
<b>Display</b>	3.5' IPS LCD Display Capacitive touch screen interface
<b>Barcode Reader</b>	Integrated QR barcode scanner
<b>Peripheral Ports</b>	USB-C, dual role port capacity of powering expansion modules. MDB Port
<b>Compliances</b>	CE, FCC, RoHS, WEEE, EMVCo MasterCard, Visa and PCI
<b>Environmental</b>	Operating temperature -4 to 131°F (-20 to 55°C) Storage temperature -4 to 158°F (-20 to 70°C) Humidity 10 to 90 RH Non-condensing IK 9 'vandal' proof
<b>Weight and Dimensions</b>	17 lbs., 52.4 in. (1331mm) x 5.85 in. (148.6mm) x 6 in. (152.4mm)
<b>Part Number</b>	EVC0411



Visit [evocharge.com](http://evocharge.com) for more information or to download installation manual.